



1.800.225.2948

Sales@KinsleyCarpets.com

PHYSICAL CONSTRUCTION

Product Type 100% SYNTHETIC FIBER PAD WITH MOISTURE BARRIER
Weight COMES IN 20, 28, 32 and 40 oz.
Thickness 245, .300, .360, .420 (RESPECTIVELY)
Density 6.2, 7.7, 8.5, 9.1 lb (RESPECTIVELY)
Width 12'
Roll Length 60'
Square Yards/Roll 80'
Recycled Content MADE OF 100% RECYCLED SYNTHETIC FIBERS
Manufacture Location TUNNEL HILL, GA 30755 USA

PERFORMANCE*

Pill Test PASSES
Radiant Panel CLASS 1

SERVICE**:

Warranty 10 YEAR UNLIMITED WARRANTY

ADDITIONAL BENEFITS:

- RECOMMENDED CARPET PAD FOR ALL COMMERCIAL USE
• CONTRUCTED TO RESIST MOISTURE AND MILDEW, ALLOWING INSTALLATION BELOW GRADE
• SUPERIOR STRENGTH TO RETAIN ITS DENSITY AND RESIST BREAKDOWN FROM MOISTURE AND WEAR
• OFFERS GREATER RESILIENCY THAN NATURAL FIBER CUSHIONS TO ENHANCE LIFE OF CARPET AND EFFECTIVENESS OF VACUUM CLEANING
• PROVIDES ADDED THERMAL AND ACCOUSTICAL INSULATION FOR IMPROVED GUEST SATISFACTION
• ALLOWS EASE OF CARPET MAINTENANCE AND THE USE OF WET CLEANING METHODS
• PROTECTS THE CARPET FROM DELAMINATING
• MEETS OR EXCEEDS FHA-HUD FLAMMABILITY REQUIREMENTS
• PROVIDES MORE COMFORT UNDERFOOT THAN DIRECT GLUE DOWN INSTALLATIONS
• NON-ALLERGENIC, ODORLESS
• SLICK SURFACE FOR EASE OF CARPET INSTALLATION