



1.800.225.2948

Sales@KinsleyCarpets.com

PHYSICAL CONSTRUCTION

Construction ..... RECYCLED RUBBER SPORTS FLOORING
Overall Thickness ..... 3/8" (CUSTOM THICKNESS AVAILABLE)
Roll Width..... 4 ft
Roll Length ..... 25 ft (CUSTOM ROLL LENGTHS AVAILABLE)
Tile Size ..... 24"W x 24"L
Installation ..... GLUE OR INTERLOCKING
Granulate ..... COLOR-1-3-mm EPDM; BLACK-8/16 SBR/VULCANIZED RUBBER CRUMB
Binder ..... URETHANE
Warranty ..... ONE YEAR BY MANUFACTURER MATERIALS
Adhesive ..... URETHANE BASE RECOMMENDED

FORMULA

Density ..... 65 lbs. Cubic Ft ..... Width = +/- 1/4"
Tensile (machine direction) ..... 250 PSI ..... 36" Cut at 36.5 +/-
Elongation at Break ..... 100% ..... 48" Cut at 48.5 +/-
Tear ..... 70 PPI DIE C ..... Thickness +/- .020

TYPICAL SPECIFICATIONS

Shore Hardness ..... ASTM-D-2240 ..... 60 +/- 5
Density ..... ASTM-D-792 ..... 65 lbs. Cubic Ft.
Elongation ..... ASTM-D-412 ..... 100%
Tensile ..... ASTM-D-412 ..... 250 PSI
Taber Abrasion ..... ASTM-D-3884 ..... 0.47
Flame Spread ..... ASTM-D-84 ..... 135
Smoke Density ..... ASTM-D-84 ..... <450
Compression Set ..... ASTM-D-395 ..... 8.40%
VOC Emissions ..... ASTM-D-5116 ..... 5 mg/m2 or less
Resistance to Chemicals ..... ASTM-F925-02 ..... No Change
Static Load Limit ..... ASTM-F970-00 ..... -0.001 in.

Ammonia-Good Disinfectant-Good Alcohol-Good Petroleum Oils-Good Anti-Microbial
Bleach-Good Human Sweat-Good Alkaline Base-Good Oxidizing Acids-Weak Mildew Resistant