

PRODUCT SPECIFICATIONS

PHYSICAL CONSTRUCTION

Style: INNOVATIVE
Construction: TUFTED—ELECTRA SERVO (LCL) ENHANCED MULTI-LEVEL SCROLL
Fiber Content: 100% SOLUTION DYED KINSLON P.E.T.
Tufted Pile Weight: 32 OZ. PER SQ. YARD
Width: 12' (CUSTOM WIDTHS AVAILABLE)
Gauge: 1/12"
Pile Height: 1/4" CUT, 1/4" LOOP
Content Ratio: 60% CUT, 40% LOOP
Stitch Rate: 39 PER 3 INCHES
Density: 9035
Pattern Repeat: 18 " W X 18 " L
Primary: SYNTHETIC WOVEN POLYPROPYLENE
Secondary: HEAVY DUTY ACTIONBAC®
Total Weight: 72 OZ. PER SQ. YARD
Recycled Content: KINSLON FIBER EXTRUDED FROM USED P.E.T. BOTTLES
Manufacture Location: TUNNEL HILL, GA 30755 USA

SERVICE

Warranty: 10 YEAR LIMITED WEAR WARRANTY

PERFORMANCE

Pill Test: PASSES
Radiant Panel: CLASS 1
NBS Smoke Density: LESS THAN 450

ADDITIONAL INFORMATION

- Carpet should be installed in accordance with the carpet and rug institute's standard CRI-104.
- The equipment used to manufacture patterned carpet may create visible lines in both length and width directions. It is not a carpet defect but is inherent in solution dyed graphic and cut/loop patterns.
- To validate warranty, carpet must be installed over manufacturer's recommended pad.