



PRODUCT SPECIFICATIONS

PHYSICAL CONSTRUCTION

Style: INTERSTELLAR

Construction: TUFTED-ELECTRA SERVO (LCL) ENHANCED MULTI-LEVEL SCROLL

Fiber Content: 100% SOLUTION DYED KINSLON P.E.T.

Tufted Pile Weight: 32 OZ. PER SQ. YARD

Width: 12' (CUSTOM WIDTHS AVAILABLE)

Gauge: 1/12"

Pile Height: 1/4" CUT, 1/4" LOOP

Content Ratio: 60% CUT, 40% LOOP

Stitch Rate: 39 PER 3 INCHES

Density: 9035

Pattern Repeat: 18 "WX18"L

Primary: SYNTHETIC WOVEN POLYPROPYLENE

Secondary: HEAVY DUTY ACTIONBAC®

Total Weight: 72 OZ. PER SQ. YARD

Recycled Content: KINSLON FIBER EXTRUDED FROM USED P.E.T. BOTTLES

Manufacture Location: TUNNEL HILL, GA 30755 USA

SERVICE

Warranty: 10 YEAR LIMITED WEAR WARRANTY

PERFORMANCE

Pill Test: PASSES

Radiant Panel: CLASS 1

NBS Smoke Density: LESS THAN 450

ADDITIONAL INFORMATION

- Carpet should be installed in accordance with the carpet and rug institute's standard CRI-104.
- The equipment used to manufacture patterned carpet may create visible lines in both length and width directions. It is not a carpet defect but is inherent in solution dyed graphic and cut/loop patterns.
- To validate warranty, carpet must be installed over manufacturer's recommended pad.